

KABELOVÁ VÝVODKA MOSAZNÁ IP68

Číslo výrobku: HSK-MM / HSK-MP

Teplotní rozsah: -30 °C + 120 °C

Krytí : IP 68 - 5 barů

MATERIÁL:

Tělo vývodky: poniklovaná mosaz

Svěrná vložka: polyamid PA6.6GF10


Vnitřní tvarová vložka: CR

O-kroužek : NBR-Oz



M

kat.č	závit F	O kabelu (mm)
HSK-MM12	M12 x 1,5	3,0 ÷ 6,5
HSK-MM16	M16 x 1,5	5,5 ÷ 10,0
HSK-MM20	M20 x 1,5	6,0 ÷ 12,0
HSK-MM25	M25 x 1,5	11,0 ÷ 18,0
HSK-MM32	M32 x 1,5	15,0 ÷ 21,0
HSK-MM40	M40 x 1,5	19,0 ÷ 27,0
HSK-MM50	M50 x 1,5	26,0 ÷ 35,0
HSK-MM63	M63 x 1,5	39,0 ÷ 48,0



PG

kat.č	závit F	O kabelu (mm)
HSK-MP7	7	3,0 ÷ 6,5
HSK-MP9	9	5,5 ÷ 10,0
HSK-MP11	11	5,5 ÷ 10,0
HSK-MP13	13,5	8,0 ÷ 13,0
HSK-MP16	16	8,0 ÷ 14,0
HSK-MP21	21	11,0 ÷ 18,0
HSK-MP29	29	19,0 ÷ 27,0
HSK-MP36	36	26,0 ÷ 35,0
HSK-MP42	42	26,0 ÷ 35,0
HSK-MP48	48	39,0 ÷ 48,0



EMC

KABELOVÁ VÝVODKA MOSAZNÁ IP68 EMC

Číslo výrobku: HSK-MM E / HSK-MP E

Teplotní rozsah: -30 °C + 120 °C

Krytí : IP 68 - 5 barů


MATERIÁL:

Tělo vývodky: poniklovaná mosaz

Svěrná vložka: polyamid PA6.6GF10


Vnitřní tvarová vložka: CR

O-kroužek : NBR-Oz



M

kat.č	závit F	O kabelu (mm)
HSK-MM12E	M12 x 1,5	3,0 ÷ 6,5
HSK-MM16E	M16 x 1,5	5,5 ÷ 10,0
HSK-MM20E	M20 x 1,5	8,0 ÷ 13,0
HSK-MM25E	M25 x 1,5	11,0 ÷ 18,0
HSK-MM32E	M32 x 1,5	15,0 ÷ 21,0
HSK-MM40E	M40 x 1,5	19,0 ÷ 27,0
HSK-MM50E	M50 x 1,5	26,0 ÷ 35,0
HSK-MM63E	M63 x 1,5	39,0 ÷ 48,0



PG

kat.č	závit F	O kabelu (mm)
HSK-MP7E	7	3,0 ÷ 6,5
HSK-MP9E	9	5,5 ÷ 10,0
HSK-MP11E	11	5,5 ÷ 10,0
HSK-MP13E	13,5	8,0 ÷ 13,0
HSK-MP16E	16	8,0 ÷ 14,0
HSK-MP21E	21	11,0 ÷ 18,0
HSK-MP29E	29	19,0 ÷ 27,0