



KABELOVÁ VÝVODKA Z NEREZOVÉ OCELI IP68 *

íslo výrobku: HXR
Krytí : IP68
Teplotní rozsah: -20 °C + 100 °C

CHARAKTERISTICKÉ VLASTNOSTI:

Vyrobeno z nerezové oceli AISI 303 (X8CrNi 1809 1.4305),
t sn ní NBR. Odolnost ionizujícímu zá ení 2x106 Gray.
Závit metrický a PG



kat.	závit F	O kabelu (mm)	CH1 mm	CH2 mm	LF mm
HXR-M08A	M8 x 1,25	2,5 ÷ 3,5	11,00	11,00	10
HXR-M08B	M8 x 1,25	3,5 ÷ 5,0	11,00	11,00	10
HXR-M10A	M10 x 1,5	3,0 ÷ 4,0	13,00	13,00	10
HXR-M10B	M10 x 1,5	4,0 ÷ 6,0	13,00	13,00	10
HXR-M12A	M12 x 1,5	3,5 ÷ 5,0	17,00	17,00	10
HXR-M12B	M12 x 1,5	5,0 ÷ 6,5	17,00	17,00	10
HXR-M12C	M12 x 1,5	6,5 ÷ 8,0	17,00	17,00	10
HXR-M16A	M16 x 1,5	8,0 ÷ 10,5	18,00	18,00	10
HXR-M20A	M20 x 1,5	11,0 ÷ 15,0	24,00	24,00	10
HXR-M25A	M25 x 1,5	16,0 ÷ 20,5	30,00	30,00	11
HXR-M32A	M32 x 1,5	21,0 ÷ 25,5	36,00	36,00	13
HXR-M40A	M40 x 1,5	28,5 ÷ 33,0	46,00	46,00	13
HXR-M50A	M50 x 1,5	37,0 ÷ 42,0	55,00	55,00	14
HXR-M63A	M63 x 1,5	46,0 ÷ 52,0	70,00	70,00	14
HXR-M63B	M63 x 1,5	40,0 ÷ 46,0	70,00	70,00	14

M

kat.	závit F	O kabelu (mm)	CH1 mm	CH2 mm	LF mm
HXR-P07	7	4,0 ÷ 6,5	14,00	14,00	8
HXR-P09	9	5,0 ÷ 10,0	19,00	19,00	8
HXR-P11	11	5,0 ÷ 12,0	22,00	22,00	8
HXR-P13	13,5	8,0 ÷ 15,0	24,00	24,00	8
HXR-P16	16	8,0 ÷ 15,0	24,00	24,00	8
HXR-P21	21	11,0 ÷ 20,5	32,00	32,00	8
HXR-P29	29	18,0 ÷ 25,5	41,00	41,00	10
HXR-P36	36	25,0 ÷ 35,0	50,00	50,00	10



PG

KABELOVÁ VÝVODKA Z NEREZOVÉ OCELI IP68 *

íslo výrobku: HXS
Krytí : IP68
Teplotní rozsah: -25 °C + 120 °C

CHARAKTERISTICKÉ VLASTNOSTI:

Vyrobeno z nerezové oceli AISI 316L (X2CrNiMo 17-12-2 1.4404),
t sn ní NBR. Vnit ní t sn ní zaru uje krytí IP 68 - tlak 5 bar



kat.	závit F	O kabelu (mm)	CH1 mm	CH2 mm	LF mm
HXS-M16	M16 x 1,5	5,0 ÷ 9,0	20,00	20,00	10
HXS-M20	M20 x 1,5	8,0 ÷ 12,0	24,00	24,00	10
HXS-M25	M25 x 1,5	11,0 ÷ 16,0	30,00	30,00	10
HXS-M32	M32 x 1,5	15,0 ÷ 21,0	36,00	36,00	10
HXS-M40	M40 x 1,5	20,0 ÷ 27,0	45,00	45,00	12

M

* termín dodání na poptání